

UW IEC Group 2010: Further Infrastructure Improvements and Preparations for 300 kV Operation

Richard Bonomo^{*}, Eric Alderson, Gabriel Becerra, Logan Campbell, David Donovan, Gil Emmert, Lauren Garrison, Gerald Kulcinski, Aaron McEvoy, Matthew Michalak, John Santarius, Craig Schuff, Sam Zenobia[#]
University of Wisconsin – Madison IEC Group

*U.S. -- Japan 2010 IEC Workshop
Osaka, Japan*

* correspondence author. e-mail address: bonomo@engr.wisc.edu

now with the NNSA, Washington, D.C. USA



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Presentation Outline

1. Current Status
2. Laboratory configuration and basic operation
3. Preparations for 300 kV operation
4. Other infrastructure improvements

Prof. Gerald Kulcinski provided an overview of experiments in progress this morning.



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Current Status of Laboratory

- Personnel:
 - 7 graduate students
 - 1 staff engineer/researcher/laboratory manager
 - 1 undergraduate technician/researcher
 - 4 faculty



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Current Status of Laboratory (as of October 2010)

- Apparatus
 - 3 operating IEC devices
 - 1 operating materials testing device
 - 1 pulsed device under construction
 - 300 kVDC power supply
 - 2-channel low-ripple filament-heating-and-bias power supply




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Laboratory Layout

FTI Primary Laboratory B151 ERB

Total floor area (incl. brick wall) 730 sq ft / 68 sq m




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Laboratory Apparatus


HELIOS



HOMER



^3He CTRE / SIGFE




MITE-E




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

HOMER (schematic view)



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Data Flow (typical)



Data are analyzed using a number of software packages available in the laboratory and at the college computing facility



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group


300 kVDC Power Supply installed May 2009



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Motivation for Power Supply Upgrade

- Improved access to ${}^3\text{He}$ - ${}^3\text{He}$ Fusion Regime




Source: J. F. Santarius



University of Wisconsin -- Madison
 Fusion Technology Institute
 Inertial Electrostatic Confinement Group

Motivation for Power Supply Upgrade

- Neutron flux appears to be monotonically increasing with voltage (greater voltage ==> more neutrons)




Graph courtesy of David Donovan



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Motivation for Power Supply Upgrade

- Neutron flux appears to be monotonically increasing with current (greater current ==> more neutrons)



Graph courtesy of David Donovan




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Replacement of high-voltage electrical vacuum feed-through

Current System



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Replacement of high-voltage electrical vacuum feed-through


Current System

Metal oil-filled chamber

Swagelok fitting

Compression nut


Boron Nitride cylinder



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Replacement of high-voltage electrical vacuum feed-through



Failed stalk from a previous year, showing burn-through from arcing




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Replacement of high-voltage electrical vacuum feed-through

New System: a metal-free feed-through




Quartz chosen for its high purity, tolerance of high temperatures (min 1000C), and high mechanical strength (1000psi tensile strength)



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Replacement of high-voltage electrical vacuum feed-through



New System

HV cable (coaxial)

PVC elements

Threaded rod

Conductor coupling

Quartz vessel

Vacuum chamber top cover

Boron nitride stalk and molybdenum rod



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Device Switching



(New) 300 kVDC cable, left, and (current) 200 ,VDC cable, right



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Device Switching

- The current practice is to switch the HV power supply between devices by physically detaching and re-attaching a cable from a junction in an oil-filled barrel.
- The larger and much-less flexible cable which will be used at the higher voltages cannot be used in this way for an extended period.
- Space constraints have also made it much more difficult to switch in the resistor-capacitor network needed to operate the devices in pulse mode.
- The group decided to design and construct a high-voltage switch, to allow the HV PS to be switched (while “off”) between the various experiments without moving cables, and to incorporate the pulse mode network into the design.



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Device Switching: Proposed HV Switch

Switch specifications:


- Switching at 0 volts (not “live” switching)
- Able to handle 300 kV DC
- Device terminals not in use must be “safed” (grounded)
- Pulse capacitor and resistors to be internal to the enclosure



Preparations for 300 kV Operation

Device Switching

Proposed High-Voltage Switch



Power input cable

Device power cable (1 of 4)

Rotating device selector ("hot")

Device terminal (1 of 4)

Raise-able / lower-able
contact bridge (1 of 4)

Pulse-enabling switch

Pulse-enabling capacitor




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Preparations for 300 kV Operation

Device Switching

Proposed High-Voltage Switch



Resistance selector
(0 to 250 k Ω in 50 k Ω increments)

Resistor strings
(5 strings of 250 k Ω each)

Current Status:


- Design studies, including field analysis using Maxwell 3-D complete
- Components and material are being acquired



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

^3He Trapping and Recovery



- Intentions to deploy a trapping system have been advanced.
- Helium-effective turbo-molecular pump, sealed backing pump, and storage cylinder have been obtained.



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

HELIOS Helicon Ion Source

Improved ion source with glass-to metal seal in under construction



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Additional Infrastructure Improvements

- Additional steps have been made toward establishing a single ground point for the laboratory, with more steps coming
- Ad-hoc facilities to electroform copper parts for the high-voltage switch are being established



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Concluding Remarks

- The laboratory should be able to expand the operating regime (cathode voltage to 300 kV) within the next year
- The improved switching system should permit the continued rapid switching between devices and experiments, and greatly reduce the time and effort required to set up pulsed experiments




University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group

Questions?



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group


Quartz Vessel




- Quartz chosen for its high purity, high heat capacity (min 1000C), and high mechanical strength (1000psi Tensile Strength)
- Base is 1” thick
- Ridges on bottom are 0.5” high, provide additional 3” of path length
- All edges are rounded to minimize sharp points
- Height of cylinder above base is 5”



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group



University of Wisconsin -- Madison
Fusion Technology Institute
Inertial Electrostatic Confinement Group



- Primary Breakdown concerns
 - Through materials
 - Along surface
- Minimum 4" radial distance between HV and Ground
 - Minimum 2" PVC, 1" Oil
- At least 4 relevant surface paths
 - Minimum recommended path length for 300kV is 15", conservatively
 - Minimum achievable in current design is 12.5"
- Two tier design to maximize path length up the HV cable

